

## SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015

Date Prepared : 12/04/2015

### Pit Fill Spot Putty

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Pit Fill Spot Putty  
**Product Code:** 4236  
**Product Description:** Glazing and Spot Putty, Beige, 290 ml / 9.8 fl oz US  
**General Use:** Body Filler - Vehicle Refinishing Product. For Professional and Industrial Use Only.  
Not for sale to the general public.  
**Chemical Family:** Solvent-based / à base de solvant  
**Molecular Formula:** Mixture / Mélange

#### Manufacturer / Supplier

Transtar Autobody Technologies  
2040 Heiserman Drive  
Brighton, MI 48114  
www.tat-co.com  
**Business Phone:** 800-824-2843

#### Emergency Telephone Numbers (24 hour)

CHEMTREC North America: (800) 424-9300  
CHEMTREC International: +1 703 527 3887

#### 2. HAZARDS IDENTIFICATION

##### GHS CLASSIFICATIONS

##### Health:

Skin Irritation, Category 2  
Specific Target Organ Toxicity - Single Exposure, Category 3 (Narcotic Effects)  
Specific Target Organ Toxicity - Repeated Exposure, Category 2  
Reproductive Toxicity, Category 1  
Carcinogenicity, Category 2

##### Physical:

Flammable Liquids, Category 2

##### GHS LABEL

Hazardous components for labelling:

**Toluene, n-Butyl acetate, Methyl ethyl ketone, Isopropyl alcohol, Dioctyl phthalate and Talc**



Exclamation mark



Flame



Health hazard

**SIGNAL WORD:** DANGER

##### HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.

## Pit Fill Spot Putty

---

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to central nervous system through prolonged or repeated exposure.

H360: May damage fertility or the unborn child.

H351: Suspected of causing cancer.

### PRECAUTIONARY STATEMENT(S)

#### Prevention:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical / ventilating / lighting equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P260: Do not breathe vapours.

P271: Use only outdoors or in a well-ventilated area.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves and eye protection.

#### Response:

P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P370+P378: In case of fire: Use dry chemical or foam to extinguish.

#### Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P233: Keep container tightly closed.

P405: Store locked up.

#### Disposal:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

### Emergency Overview

#### Immediate Concerns:

Flammable liquid and vapor. Irritating to eyes and skin. Vapours may cause drowsiness and dizziness.

Overexposure may cause nerve damage. Possible risk of harm to the unborn child. Suspected of causing cancer.

#### Hazards Not Otherwise Classified:

No data available.

#### Comments:

<5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS No.
Talc	38 - 42	14807-96-6
Toluene	17 - 21	108-88-3
n-Butyl acetate	6 - 8	123-86-4
Diethyl phthalate	3 - 5	117-81-7
Methyl ethyl ketone	2 - 4	78-93-3
Isopropyl alcohol	1 - 3	67-63-0

**Comments:** There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

### 4. FIRST AID MEASURES

**Eye Contact:**

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

**Skin Contact:**

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

**Ingestion:**

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

#### Signs and Symptoms of Overexposure

**Eye Contact:**

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**Skin Contact:**

Contact causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Ingestion:**

Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea. Poison, May be fatal or cause blindness if swallowed. May cause aspiration and lung damage.

**Inhalation:**

High vapor or spray mist concentrations may be harmful if inhaled. May cause headaches and dizziness. High vapor concentrations may cause drowsiness.

**Notes to Physician:**

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

**Additional Information:**

No data available.

## **5. FIRE FIGHTING MEASURES**

### **Flammable Properties:**

Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point. Product can be ignited by static discharge.

### **Extinguishing Media:**

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

### **Hazardous Combustion Products:**

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

### **Fire Fighting Procedures:**

Containers can build up pressure if exposed to heat (fire).

### **Fire Fighting Equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

### **Sensitivity to Static Discharge:**

Product is sensitive to static discharge.

### **Sensitivity to Mechanical Impact:**

Product is not sensitive to mechanical impact.

## **6. ACCIDENTAL RELEASE MEASURES**

### **Small Spill:**

Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

### **Environmental Precautions**

#### **Water Spill:**

Do not flush to sewer.

#### **Land Spill:**

Avoid runoff into storm sewers and ditches which lead to waterways.

### **Special Protective Equipment:**

Clean up spills immediately, observing precautions in Protective Equipment section 8.

## **7. HANDLING AND STORAGE**

### **General Procedures:**

Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids. Ensure thorough ventilation of stores and work areas.

### **Handling:**

Do not use in the presence of open flame or spark. Use only in a well ventilated area. Wear recommended personal protective equipment. Keep container closed when not in use. Avoid breathing vapours or mist. Avoid contact with eyes, skin, and clothing. After handling, always wash hands thoroughly with soap and water.

### **Storage:**

Store away from heat, sparks, open flames, strong oxidizing agents and direct sunlight. Protect from physical damage. Keep container tightly closed and in a well-ventilated place. Store in a cool place.

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

## Pit Fill Spot Putty

### Exposure Guidelines

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		Occupational Exposure Limits					
		OSHA PEL		ACGIH TLV		NIOSH REL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Talc	<b>TWA</b>	-- [1]	2 [1]	-- [1]	2 [1]	-- [1]	2 [1]
Toluene	<b>TWA</b>	200	--	50	188	100	375
	<b>STEL</b>	300	--	--	--	150	560
n-Butyl acetate	<b>TWA</b>	150	710	150	713	150	710
	<b>STEL</b>	[2]	[2]	200	950	200	950
Diethyl phthalate	<b>TWA</b>	--	5	--	5	--	5
	<b>STEL</b>	--	5	[2]	[2]	--	10
Isopropyl alcohol	<b>TWA</b>	400	980	200	490	400	980
	<b>STEL</b>	[2]	[2]	400	960	500	1225

**Footnotes:**  
1. Dust - respirable fraction.  
2. NL: This material does not have established exposure limits.

### Engineering Controls:

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

### Personal Protective Equipment

#### Eyes and Face:

Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

#### Skin Contact:

Wear chemical resistant gloves.

#### Respiratory:

If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

#### Protective Clothing:

Wear protective clothing as necessary to prevent contact.

### Work Hygienic Practices:

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State</b>	: Liquid
<b>Odor</b>	: Aromatic
<b>Odor Threshold</b>	: No data available.

## Pit Fill Spot Putty

---

<b>Appearance</b>	: Thixotropic
<b>Color</b>	liquid : Beige
<b>pH</b>	: Not Applicable
<b>% Volatiles</b>	: 30 to 32 % w/w
<b>Flash Point and Method</b>	: 16°C (61°F) Closed Cup
<b>Flammable Limits</b>	: 1.1 to 7.1
<b>Notes:</b> Based on data for toluene.	
<b>Autoignition Temperature</b>	: > 400°C (752°F)
<b>Vapor Pressure</b>	: 78 mm Hg [Methyl Ethyl Ketone] at 20°C
<b>Vapor Density</b>	: > 1 (air = 1)
<b>Boiling Point</b>	: 80°C (176°F) (Methyl Ethyl Ketone)
<b>Freezing Point</b>	: No data available.
<b>Melting Point</b>	: No data available.
<b>Solubility in Water</b>	: Partial
<b>Evaporation Rate</b> (n-butyl acetate = 1)	: > 1
<b>Density</b>	: 1.55±0.03g/ml at 20°C
<b>Viscosity</b>	: > 100000 cps
<b>VOC Content</b>	: <500 g/l (4.17 lb/gal), less exempt solvents
<b>Oxidizing Properties</b>	: None

## 10. STABILITY AND REACTIVITY

**Reactive Hazard** : No

**Hazardous Polymerization:**

Not expected to occur.

**Stability:**

Stable.

**Conditions to Avoid:**

Keep away from flames and any object that sparks.

**Possibility of Hazardous Reactions:**

Not Available

**Hazardous Decomposition Products:**

Carbon Monoxide and other toxic vapors.

**Incompatible Materials:**

Oxidizing materials.

## 11. TOXICOLOGICAL INFORMATION

### Product Acute Toxicity

## Pit Fill Spot Putty

Chemical Name	ORAL LD <sub>50</sub> mg/kg (rat)	DERMAL LD <sub>50</sub> mg/kg (rabbit)	INHALATION LC <sub>50</sub> mg/l
Talc	Not classified.	Not classified.	Not classified.
Toluene	7000, 6400, 5500	12,270	49.0(rat;4h) 30.0(mouse;2h) 19.9(mouse;7h)
n-Butyl acetate	13,100(rat) 11,000(rat)	>14,400	>45.0(rat;4h)
Diocetyl phthalate	>25,000(rat) >30,000(mouse) 33,900(rbt)	25,000	No data available.
Methyl ethyl ketone	3400(rat) 2900(rat) 5520(rat) 3140(mouse)	>8000	34.5(rat;4h) [11,700 ppm] >5000 ppm (rat;6h)
Isopropyl alcohol	4710-5840 4475(mouse) 5030(rabbit)	12,870	51.0(rat;8h) 72.6(rat;4h)

**Acute Toxicity - Dermal LD<sub>50</sub>:** The calculated ATE is >2000 mg/kg.

**Notes:**

Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture.

**Acute Toxicity - Oral LD<sub>50</sub>:** The calculated ATE is >2000 mg/kg.

**Notes:**

Based on available data, the classification criteria for Acute Oral Toxicity are not met for this mixture.

**Acute Toxicity - Inhalation LC<sub>50</sub>:** The calculated ATE is >20 mg/l/4h (vapours) and >5 mg/l/4h (mists).

**Notes:**

Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture.

**Toxicological Data:**

< 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

No additional toxicology information is available for this product itself. (See Component Toxicity Information).

**Eye Irritation / Serious Eye Damage:**

Contains: Methyl ethyl ketone and Isopropyl alcohol. Based on available data, the classification criteria for eye irritation are not met for this mixture. Slightly irritating but does not injure eye tissue.

**Skin Irritation / Corrosion:**

Contains: Toluene. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Carcinogenicity**

## Pit Fill Spot Putty

Chemical Name	NTP Status	IARC Status	OSHA Status	Other
Talc	--	3	--	A4 (ACGIH)
Toluene	--	3	--	--
n-Butyl acetate	--	--	--	--
Diethyl phthalate	P	3	--	A3 (ACGIH)
Methyl ethyl ketone	--	--	--	--
Isopropyl alcohol	--	3	--	--

### Notes:

The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as a Carcinogen, category 2).

### Specific Target Organ Toxicity - Repeated Exposure:

The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ( $\geq 1.0\%$  ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged inhalation may be harmful. Chronic exposure to organic solvents such as Toluene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

### Respiratory / Skin Sensitizer.:

Based on available data, the classification criteria for skin/respiratory sensitization are not met for this mixture ( $< 0.1\%$  ingredients classified as a skin sensitizer, category 1 or sub-category 1A and  $< 1.0\%$  ingredients classified as a skin/respiratory sensitizer, sub-category 1B).

### Reproductive Toxicity:

Contains: Toluene and Diethyl phthalate. The mixture is classified as: Reproductive Toxicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as Reproductive Toxicity, category 2). May damage the unborn child. Suspected of damaging fertility.

### Specific Target Organ Toxicity - Single Exposure:

Contains: Toluene, Methyl ethyl ketone, n-Butyl acetate and Isopropyl alcohol. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ( $\geq 20\%$  summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3). Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

### Germ Cell Mutagenicity:

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture ( $< 0.1\%$  ingredients classified as Germ Cell Mutagen, category 1A or 1B and  $< 1.0\%$  ingredients classified as Germ Cell Mutagen, category 2).

### Aspiration Hazard:

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ( $< 10\%$  ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity  $> 20.5 \text{ mm}^2/\text{s}$  at  $40 \text{ }^\circ\text{C}$ ).

## 12. ECOLOGICAL INFORMATION

### Environmental Data:

No data available.

### Ecotoxicological Information:

No data available.



## Pit Fill Spot Putty

---

**Bioaccumulation/Accumulation:**

No data available.

**Distribution:**

No data available.

**Aquatic Toxicity (Acute):**

No data available.

**Chemical Fate Information:**

No data available.

### 13. DISPOSAL CONSIDERATIONS

**Disposal Method:**

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

**Product Disposal:**

Empty containers retain product residue; observe all precautions for product. Decontaminate containers prior to disposal.

### 14. TRANSPORT INFORMATION

**DOT (Department of Transportation)**

**Proper Shipping Name** : FLAMMABLE LIQUID, N.O.S.

**Technical Name** : Toluene

**Primary Hazard Class/Division:** 3

**UN/NA Number** : 1993

**Packing Group** : II

**Other Shipping Information:**

For products with an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

**Vessel (IMO/IMDG)**

**Shipping Name** : FLAMMABLE LIQUID, N.O.S.

**Technical Name** : Toluene

**UN/NA Number** : 1993

**Primary Hazard Class/Division:** 3

**Packing Group** : II

**Marine Pollutant** : None

**Note:** For products with an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

**Canadian Transportation of Dangerous Goods Regulations**

**Shipping Name** : FLAMMABLE LIQUID, N.O.S.

**Technical Name** : Toluene

**UN/NA Number** : 1993

**Primary Hazard Class/Division:** 3

**Packing Group** : II

**TDG Note:**

## Pit Fill Spot Putty

For products with an inner packaging < 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

### 15. REGULATORY INFORMATION

#### UNITED STATES

##### SARA Section 311/312 Hazard Categories

**Fire Hazard** : Yes  
**Sudden Release of Pressure** : No  
**Reactive Hazard** : No  
**Product Acute Toxicity** : Yes  
**Product Chronic Toxicity** : Yes

##### EPCRA Section 313 Toxic Chemicals

Chemical Name	Wt. %	CAS No.
Toluene	17 - 21	108-88-3
Diethyl phthalate	3 - 5	117-81-7
Isopropyl alcohol	1 - 3	67-63-0

##### EPCRA Section 302 Extremely Hazardous Substances

###### EPCRA Status:

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

##### CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical Name	Wt. %	RQ
Toluene	17 - 21	1,000
n-Butyl acetate	6 - 8	5,000
Diethyl phthalate	3 - 5	100
Methyl ethyl ketone	2 - 4	5,000

##### TSCA (The Toxic Substances Control Act)

###### TSCA Status:

All components are included or are otherwise exempt from inclusion on this inventory.

##### CAA 112(b) - Hazardous Air Pollutants

Chemical Name	Wt. %	CAS No.
Toluene	17 - 21	108-88-3
Methyl ethyl ketone	2 - 4	78-93-3

##### CAA 112(r) - List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(r).

##### California Proposition 65

## Pit Fill Spot Putty

Chemical Name	Wt. %	Listed
Toluene	17 - 21	<ul style="list-style-type: none"><li>• Developmental Toxicity</li><li>• Female Reproductive</li></ul>
Diethyl phthalate	3 - 5	<ul style="list-style-type: none"><li>• Cancer</li><li>• Developmental Toxicity</li></ul>

### OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

## CANADA

### WHMIS Hazard Symbol and Classification

See Section 2 for details.

### WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

### WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

### CEPA - National Pollutant Release Inventory (NPRI):

Name	CAS No.	NPRI Part No.
Toluene	108-88-3	1A, 5 (VOC)
Methyl Ethyl Ketone	78-93-3	1A, 5 (VOC)
Isopropyl alcohol	67-63-0	1A, 5 (VOC)
Diethyl phthalate	117-81-7	1A

### Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

### Comments

VOC Content -- See section 9.

## 16. OTHER INFORMATION

**Reason for Issue:** NEW


**Prepared By :** Transtar Autobody Technologies

**Date Prepared:** 12/04/2015

**HMIS RATING**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>G</b>

**NFPA CODES**



**NFPA 30 / 30B Storage Classification:** Flammable Liquid IB

**Manufacturer Supplemental Notes:**

None

**Data Sources:**

Not Available

**Additional MSDS Information:**

- N/AV Not Available
- N/AP Not Applicable
- ND Not yet determined
- CAA The Clean Air Act
- CCCR The Consumer Chemicals and Containers Regulations
- CEPA The Canadian Environmental Protection Act
- CERCLA Comprehensive Environmental Response, Compensation, and Liability Act
- EPCRA The Emergency Planning and Community Right-To-Know Act
- IARC International Agency for Research on Cancer
- MSHA Mine Safety and Health Administration
- NIOSH National Institute for Occupational Safety and Health
- NTP National Toxicology Program
- OSHA The Occupational Safety and Health Act
- SARA The Superfund Amendments and Reauthorization Act
- WHMIS Workplace Hazardous Materials Information System

**General Statements:**

None

**Comments:**

None

**Manufacturer Disclaimer:**

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.