



Super Kut Compound

5321, 5324

Ultimate Finish System™ Super Kut Compound is an aggressive compound that removes scratches and imperfections in difficult substrates and coatings. It produces a high gloss and shine on gel coat, hard-baked coatings, scratch resistant coatings, etc. Safe for use on all paints.

A

Mix Ratio

Mix Ratio: Ready to use

Surface Prep & Application

Wash surface to be sanded with soap and water. Sand 1000 grit, wet or dry until imperfections or defects are removed. Finish sand with 1200-1500 grit.

Do not apply in direct sunlight. Shake well before use. Wash and degrease surface to be compounded. Apply enough material to work a 2'x2' area. Using a Wool Compound Pad (5200 or 5260) or Orange Cutting Compound Pad (5272) on a mechanical buffer (1800 - 2200 rpm) begin working the material with moderate pressure. Keep buffer moving to prevent burn-through. To reduce sling, spread the material before buffing. Use additional applications as necessary. Continue with Tri-Cut II 5331/5334 or Cutting Compound 5361/5364 for a deep finish and shine.



Product Specifications

Color.....White
Shelf life.....3 years

Size (5321).....Gallon
(5324).....Quart

Regulatory

Category.....Automotive rubbing or polishing compound
VOC Content.....<17% by weight



Limitations & Precautions

- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.
