Cutting Compound

5361, 5364

Ultimate Finish System™ Cutting Compound features innovative, optimum-cut technology that levels 1200 grit or finer sand scratches and imperfections without scratching the paint. Safe on all paints, Cutting Compound produces a high gloss and shine on hard-baked coatings, scratch resistant coatings, gel coat and more. For best results, use with Transtar's Orange Foam Pad.

A

Mix Ratio

Mix Ratio: Ready to use

Surface Prep & Application

Wash surface to be sanded with soap and water. Sand 1200-2000 grit, wet or dry until imperfections or defects are removed. Finish sand with 1500-2000 grit.
Do not apply in direct sunlight. Shake container well before use. Apply a 1.25" wide by 6" long ribbon (for every 2' x 2' area to compound) of Cutting Compound and spread with pad to minimize sling. Using a buffer at moderate to low speed (1000-1400 rpm), work material in a circular overlapping motion using Cutting Compound Orange Foam Cutting Compound Pad 5272 or Wool Buffing Pad 5200 or 5260. Be sure to perform 50% overlapping passes and apply sufficient pressure to remove imperfections and scratches. Continue buffing until desired gloss is obtained. Care must be taken to avoid scouring the finish. After desired gloss is obtained, wash surface with soap and water and dry with a soft cloth to avoid scratching the surface. Proceed to use 5374 Machine Polish to remove fine scratches. See 5374 Technical Data Sheet for application instructions.

Product Specifications

Color	White	Size (5361)	Gallon
Shelf life	3 years	(5364)	Quart

Regulatory

Category	Automotive rubbing or polishing coumpound
VOC Content	<12% by weight

Limitations & Precautions

- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.