



Amber Rustproofing

60-4423

Amber Rustproofing matches OEM appearance while providing superior rust protection. Abrasion resistant coating will flow into hard to reach seams. Designed for replacement panels or new car rustproofing and restores the repair of existing corrosion protection to original specifications found on the interior of fender and panel replacements.



Mix Ratio

Ready to use.



Suitable Substrates

- Aluminum
- Galvanized steel
- Steel
- Non-reversible painted substrates



Surface Prep & Application

Shake well. Clean surface using SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394. Holding can 10 - 12" from the surface, apply 2 - 3 light even coats. Short, even strokes produce best results. Remove overspray with Acry Solvent 9783/9784. Note: For use with 4471, Corrosion Protection Kit - Amber Rustproofing 4423 can also be applied using the tubing, included in the 4471 kit, for inside guide rails and other hard to reach applications.

Note: Allow several hours for flammable vapors to escape when product is sprayed in enclosed areas. Flush with compressed air to help remove vapors.



Product Specifications/Regulatory

Color.....Amber	Shelf Life.....3 years
VOC Content.....<75% by weight	Size20 oz Aero

Performance Properties

Test	Condition	Result
Metal Adhesion	1 hour @ 75°F (24°C) after application	Very Good
Water Resistance	3 weeks @ 75°F (24°C)	Excellent



Limitations & Precautions

- This product provides adhesion & corrosion protection when used over noted (checked) substrates - when properly cleaned, sanded & applied.
- Not recommended for use on exposed areas such as luggage compartments or engine bays, as the material remains tacky after application.
- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.
- All Standard Operating Procedures (SOP) can be found on the Transtar website at www.tat-co.com.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.
