



Acryl Solvent

60-9783, 9784

Acryl Solvent adhesive cleaner quickly softens and removes adhesives, tar, grease, oil, body sealers, wax, undercoating overspray and silicones. Acryl Solvent can also be used as a pre-paint cleaner and conditioner, it leaves no residue on the surface and is safe for use on automotive finishes when used as directed.



Mix Ratio

Ready to use.



Surface Prep & Application

Apply directly to or saturate a clean cloth and rub/buff adhesive or solid area lightly to remove. Repeat if necessary. Note: On freshly painted surfaces use caution not to flood the surface or rub harshly to avoid damage to the finish. On areas where adhesive is thoroughly dry or contaminants are very thick, such as road tar, allow for a few minutes for the Acryl Solvent to penetrate. Repeat if necessary.



Product Specifications

Color.....	Clear	Size (60-9783).....	20 oz Aero
Shelf Life.....	5 years	(9784).....	Quart

Regulatory

9784

Category.....	Cleaner	Wt % of Volatiles.....	5 years
VOC Actual.....	6.59 #/gal (790 g/l)	Wt % of Water.....	0
VOC Regulatory.....	6.59 #/gal (790 g/l)	Wt % of Exempt Compound.....	0
Density.....	6.59 #/gal	Vol % of Exempt Compound.....	0

60-9873

Category.....	General Purpose Degreaser
VOC Content.....	100%



Limitations & Precautions

- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.
- If mixed with other components, mixture may be hazards of all combined components.
- All Standard Operating Procedures (SOP) can be found on the Transtar website at www.tat-co.com.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.