



SCAT Wax & Grease Remover 6311

SCAT is a specially formulated solvent blend for lifting and removing wax, silicone, grease and oil from surfaces to be painted. Used primarily as a pre-paint cleaner and conditioner to remove wax and silicone, SCAT leaves no residue on the surface.



Mix Ratio

Ready to use



Suitable Substrates

- Bare steel
- Bare galvanized
- Bare aluminum
- All OEM finish & old paint work
- 1K primer
- Self-etch primer
- Plastic part - primed
- 2K primer
- Body filler
- OEM E-Coat

Note: Due to the diverse nature of plastics, always test plastic substrate for acceptable adhesion. Adhesion promoter maybe required for proper adhesion.

Note: Test pre-primed panels with acetone or paint thinner. If coating fails, strip panel to bare plastic & follow SOP 251 for Raw Plastic.



Surface Prep & Application

Apply SCAT to surface prior to grinding, sanding or painting to prevent contaminants from being worked into the substrate surface. Saturate a clean cloth with SCAT. Work small areas rubbing briskly. Wipe off immediately with a clean, dry cloth. Change cloths frequently to prevent spreading of contamination. If necessary, repeat entire application until completely clean.

Note: For best results, wipe dry, do not let evaporate on panel.



Product Specifications

Color.....Clear	Size.....Gallon
Shelf life.....5 years	

Regulatory

Category.....Cleaner	Wt % of volatiles..... 100
VOC actual.....6.57#/gal (788 g/l)	Wt % of water 0
VOC regulatory.....6.57#/gal (788 g/l)	Wt % of exempt compound 0
Density.....6.57 #/gal	Vol % of exempt compound 0



Limitations & Precautions

- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.
