

Ruff Stuff and Scuff & Prep Paste

6337, 6338

Scuff & Prep Paste and Ruff Stuff are used for paint preparation and blending. Use for surface preparation prior to painting to remove contaminants, silicone, grease and oils, tar and road film. Use on all areas to be painted, panels, jambs, moldings, bumpers. To save time, use in place of wet sanding and degreasing. Use Scuff & Prep Paste for light scuffing and Ruff Stuff for heavy scuff applications.



Mix Ratio

Ready to use



Suitable Substrates

- Raw plastic rigid (SMC, BMC) Bare steel
- Raw plastic flex (ABD, PPO) Bare galvanized
- Raw plastic soft (PUR)
- Plastic part primed
- Fiberglass/SMC Gel Coat
- 1K primer
 - 2K primer
 - Body filler
 - OEM E-Coat

• All OEM finish & old paint work Note: Due to the diverse nature of plastics, always test plastic substrate for acceptable adhesion. Adhesion promoter maybe required for proper adhesion.

Note: Test pre-primed panels with acetone or paint thinner. If coating fails, strip panel to bare plastic & follow SOP 251 for Raw Plastic.

• Bare aluminum

Self-etch primer



Surface Prep & Application

Wash application area with warm water & soap prior to use. Apply Scuff & Prep Paste or Ruff Stuff to clean, wet, green/grey fine abrasive pad, cloth, or foam pad. Use circular motion and light pressure. For confined areas use a stiff brush. Rinse area off with clean water.

Note: Remember to rinse clean with water to remove any residue prior to degreasing.



Product Specifications

Color	.White paste	Size (6337)	4.5 lb tub
Shelf life	.3 years	(6338)	24 oz tube

Regulatory

Category	Automotive rubbing	or polishing	compound
VOC content	<6%		



Limitations & Precautions

- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.