

Appearance Improver

Appearance Improver is specially formulated for use in high temperatures and/ or on extremely large refinish areas. 6487 will improve flow out and appearance of all Transtar Clearcoats used in conditions where temperatures exceed 90°F (32°C) and/or large refinish areas where extended open times are required to allow adequate integration of overspray.



Surface Prep & Application

Refer to topcoat manufacture for surface preparation.

Mix with any Transtar, True Finish, Motor City or Signature Series Clearcoats to enhance the appearance in high temperature applications. Use 1 to 2 ounces per sprayable quart.



Product Specifications

Color	.Clear	Size (1391)	8 oz
Shelf life	.3 years	RTS Solids	24.6%

Regulatory

Category	N/A	Wt % of volatiles75.	.41
VOC actual	1.44#/gal (172 g/l)	Wt % of water0	
VOC regulatory	3.17#/gal (380 g/l)	Wt % of exempt compound 60.	.98
Density	9.97 #/gal	Vol % of exempt compound 54.	.62



Limitations & Precautions

- · Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- · See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE, LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.