

CP Basecoat Binder & Basecoat Balancer

7232-1D, 7233-1D

Transtar CP Basecoat Binder and CP Basecoat Balancer have been formulated as comparable offerings for the most common major manufacturer's products. Since these are similar products, they are intended for use in a comparable manner as the color formula indicates.



Surface Prep & Application

Refer to topcoat manufacture for surface preparation.

CP Basecoat Binder 7232-1D, is comparable to Axalta* 62320F Basecoat Binder and CP Basecoat Balancer, 7233-1D, is comparable to Axalta* 62330F Basecoat Balancer, (Primarily used in ChromaPremier®). These products are intended for use in a similar manner as the Axalta product.

Agitate thoroughly before use. Refer to color manufacturers formulas for required amounts. (Use the same amount of Transtar material as that indicated for the Axalta items that it replaces.) Always use accurate weights and measures.

*DISCLAIMER: ChromaBase® and ChromaPremier® Basecoat Colors are registered trademarks of Axalta Coating Systems. Axalta does not manufacture, endorse, or guarantee Transtar products.



Product Specifications

Color	Clear	Size (7232-1D Binder)	Gallon
Shelf life	3 years	(7233-1D Balancer)	Gallon

Regulatory

7232-TD CP Basecoat Balancer		Wt % of volatiles	85.54
VOC actual	6.44#/gal (772 g/l)	Wt % of water	0
VOC regulatory	6.44#/gal (772 g/l)	Wt % of exempt compound	0
Density	7.53 #/gal	Vol % of exempt compound	0
7233-1D CP Basecoat Binder		Wt % of volatiles	79.71
VOC actual	6.13#/gal (735 g/l)	Wt % of water	0
VOC regulatory	6.13#/gal (735 g/l)	Wt % of exempt compound	0
Density	7.69 #/gal	Vol % of exempt compound	0



Limitations & Precautions

- CP Basecoat Binder and CP Basecoat Balancer products MUST be sealed after each use to prevent moisture and contaminants from entering.
- To avoid applying kicked out basecoat, it is always good shop practice to spray a test panel.
- Always turn on your intermix machine for agitation first thing in the morning to ensure toners and Transtar products are sufficiently agitated which will help to avoid color mismatch issues.
- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.