



Super Wet Look

8105, 8108

Super Wet Look Acrylic Enamel Catalyst is designed for use in acrylic enamel color systems to improve flow and leveling for an improved finish. It will produce a hard, durable finish with excellent gloss and chemical resistance. Super Wet Look is designed to provide a higher level of gloss, with long-term gloss retention.



Surface Prep & Application

Refer to topcoat manufacture for surface preparation.

Reduce acrylic enamel per paint manufacturers instructions. Add Super Wet Look Acrylic Enamel Catalyst at a rate of 8 parts color to 1 part catalyst, as recommended by the paint manufacturer. Apply per paint manufacturers instructions. Clean equipment thoroughly after use.

Note: Catalyzed enamels left in spray gun will harden. Keep activator closed tightly after use, since exposure to air will cause gelation.



Product Specifications

Color.....	Clear	Size (8105).....	1/4 pint
Shelf life.....	3 years	(8108).....	Pint
RTU Solid.....	73%		

Regulatory

Category.....	Single Stage Coating	Wt % of volatiles.....	26.71
VOC actual.....	2.38#/gal (285 g/l)	Wt % of water.....	0
VOC regulatory.....	2.38#/gal (285 g/l)	Wt % of exempt compound.....	0
Density.....	8.90 #/gal	Vol % of exempt compound.....	0



Limitations & Precautions

- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.